

# CARLISLE'S AUTHORIZED APPLICATORS MARKETING ANNOUNCEMENT

**FB-2007-29**

**20-Year Sure-White® FleeceBACK® Warranty  
October 16, 2007**

TO: Carlisle Authorized Applicators

Carlisle is pleased to announce that, effective immediately, Sure-White 115-mil FleeceBACK is eligible for a 20-year Total System Warranty.

Carlisle's Sure-White FleeceBACK 20-year system with FAST™ Adhesive must meet the following guidelines (for additional information refer to Carlisle FleeceBACK Design Specification attachment IV):

- Sure-White FleeceBACK 115-mil EPDM membrane must be fully adhered with FAST™ Adhesive to the insulation or substrate.
- Membrane field splices may be completed with 3" Factory-Applied Tape™ when splices are shingled and a minimum roof slope of ¼" in 12" is provided. For slopes less than ¼" in 12" or where splices "buck" water, seams must be stripped in using 6" Sure-White Pressure Sensitive Cured Cover Strip.
- Carlisle's Sure-White Pressure Sensitive accessories must be used whenever possible (Sure-White PS Cured Flashing, Cured Cover Strip, Pipe Flashings, etc.). PS White Elastoform Flashing, PS Elastoform Corners, Flashing, PS Cured Cover Strip, PS Curb Flashing, PS Molded Pipe Seal, and PS Russ at metal counter flashings, Carlisle's Termination Bar must be installed in accordance with Carlisle Detail U-9-H.
- Metal edgings, if applicable, shall be Carlisle's SecurEdge™ 1000, 2000 or 3000.
- Treated wood nailers are not to be used in conjunction with the Sure White System. If treated wood nailers are required, a slip-sheet of cured Sure-Seal® black EPDM membrane must be used as a separator.
- Copper or other heavy metals shall not be permitted to be in direct contact with the membrane.

Please take advantage of these changes to Carlisle's Sure-White 115-mil FleeceBACK specification. If you have any questions regarding this change, please contact your Carlisle Manufacturer's Representatives and Distributors.

Sincerely,



Ronald L. Goodman  
Product Manager – FleeceBACK Systems